


# Helios WL-294-M Eco

white light illuminator with accent lighting










MICROLIGHT



Supply voltage	12...24 V AC/DC
Power consumption	28.0 W
Built-in photocell	yes
Pressure equalization valve	yes
Ingress protection	IP67, IK10
Operation temperature	-40...+50 °C
Weight	1.2 kg



Color temperature, K	5000				
Angle, °	15	30	45	60	90
Luminous flux, lm	2230				
Luminous intensity, cd	41300	10600	4650	2650	1210
Color rendering index, R <sub>A</sub>	80				
The level of light at a distance of 5 m, lx	1650	425	185	105	48
The level of light at a distance of 10 m, lx	410	105	46	26	12
The level of light at a distance of 15 m, lx	180	47	21	12	5

-  built-in current regulator
-  increased efficiency of removal of heat from the radiating elements
-  high-performance surface-mount LEDs
-  different versions based on the color temperature of light
-  tripping delay photocell to prevent accidental turn off
-  built-in photocell
-  supply voltage 185...265 V AC
-  power over ethernet (PoE+) IEEE 802.3at
-  supply voltage 12...24 V AC/DC

### Optional:

- w/o built-in photocell
- screw-thread 1/4" (1/4-20 UNC)
- PoE IEEE 802.3at (PoE+)
- supply voltage 185...265 V AC
- RAL color available

